




PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF DYTRAN INSTRUMENTS INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF DYTRAN INSTRUMENTS INC. IS PROHIBITED

VARIATION TABLE

MODEL	SENSITIVITY
3055D7	100mV/g
3055D8	50mV/g
3055D9	20mV/g
3055D10	10mV/g
3055D13	200mV/g
3055D14	500mV/g

REVISIONS

REV.	ECN	DESCRIPTION	BY/DATE	CHK	APPR
A	14614	INITIAL RELEASE. SAME AS REV X3.	KG 12/01/20	RA	DV

MOUNTING RECOMMENDATION:
PREPARE A .55 [14] X .55 [14] MIN SURFACE,
FLAT TO .001 TIR.
TAP 10-32 UNF-2B ∇ .15 [3.8] MIN.
MOUNTING TORQUE: 10-12 Lb-in.

UNLESS OTHERWISE SPECIFIED:
INTERPRET DIM & TOL PER
ASME Y14.5M - 1994.
REMOVE BURRS.
COUNTERSINK INTERNAL THDS
90° TO MAJOR DIA.
CHAM EXT THDS 45° TO MINOR DIA.
THD LENGTHS AND DEPTHS ARE FOR
MIN FULL THDS.
DIMENSIONS APPLY AFTER FINISHING.

ALL MACHINED SURFACES. $\sqrt{63}$
TOTAL RUNOUT WITHIN .005.
BREAK SHARP EDGES .005 TO .010.
MACHINED FILLET RADII .005 TO .015.
WELDING SYMBOLS PER AWS A2.4.
ABBREVIATIONS PER MIL-STD-12.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES.
DIMENSIONS IN BRACKETS [] ARE IN
MILLIMETERS TOLERANCES ARE:

DECIMALS	METRIC	ANGLES
.XX $\pm$.03	.X $\pm$ 0.8	ANGLES $\pm$ 1°
.XXX $\pm$.010	.XX $\pm$ 0.25	

APPROVALS		DATE
ORIG	LN	03/10/17
CHK		
APP		
DO NOT SCALE DRAWING		THIRD ANGLE PROJECTION USA



Chatsworth, CA




TITLE: **OUTLINE/INSTALLATION DWG,
SINGLE AXIS ACCEL, 320F,
ISOLATED, 3055D7 SERIES**

SIZE B	CAGE CODE 2W033	DWG NO 127-3055D7	REV A
SCALE: 3:1		SHEET 1 OF 1	

5. OPERATING TEMPERATURE: -67°F TO +320°F [-55°C TO +160°C]
- 4 MATES WITH DYTRAN 6010AXX OR 6011AXX CABLE (XX=LENGTH IS FEET).
3. WEIGHT: 10 GRAMS, MAX.
- 2 ARROW INDICATES ACCELERATION DIRECTION FOR POSITIVE OUTPUT.

1. MATERIAL: TITANIUM ALLOY

NOTES: UNLESS OTHERWISE SPECIFIED

Model Number 3055D13		PERFORMANCE SPECIFICATIONS				DOC NO PS3055D13																																				
		IEPE ACCELEROMETER				REV B, ECN 16090, 03/02/21																																				
		• -67 °F TO +325°F OPERATION • BASE ISOLATED • IDEAL LOW FREQUENCY RESPONSE • HERMETICALLY SEALED				This family also includes: <table><thead><tr><th>Model</th><th>Sensitivity (mV/g)</th><th>Frequency Response, ±10% (Hz)</th><th>Time Constant (Sec)</th><th>Operating Temp (°F)</th></tr></thead><tbody><tr><td>3055D7</td><td>100</td><td>1 to 10000</td><td>0.5 to 1.5</td><td>-67 to +325</td></tr><tr><td>3055D8</td><td>50</td><td>1 to 10000</td><td>0.5 to 1.5</td><td>-67 to +325</td></tr><tr><td>3055D9</td><td>20</td><td>1 to 10000</td><td>0.5 to 1.5</td><td>-67 to +325</td></tr><tr><td>3055D10</td><td>10</td><td>1 to 10000</td><td>0.5 to 1.5</td><td>-67 to +325</td></tr><tr><td>3055D14</td><td>500</td><td>1 to 10000</td><td>0.5 to 1.5</td><td>-67 to +325</td></tr></tbody></table>		Model	Sensitivity (mV/g)	Frequency Response, ±10% (Hz)	Time Constant (Sec)	Operating Temp (°F)	3055D7	100	1 to 10000	0.5 to 1.5	-67 to +325	3055D8	50	1 to 10000	0.5 to 1.5	-67 to +325	3055D9	20	1 to 10000	0.5 to 1.5	-67 to +325	3055D10	10	1 to 10000	0.5 to 1.5	-67 to +325	3055D14	500	1 to 10000	0.5 to 1.5	-67 to +325					
Model	Sensitivity (mV/g)	Frequency Response, ±10% (Hz)	Time Constant (Sec)	Operating Temp (°F)																																						
3055D7	100	1 to 10000	0.5 to 1.5	-67 to +325																																						
3055D8	50	1 to 10000	0.5 to 1.5	-67 to +325																																						
3055D9	20	1 to 10000	0.5 to 1.5	-67 to +325																																						
3055D10	10	1 to 10000	0.5 to 1.5	-67 to +325																																						
3055D14	500	1 to 10000	0.5 to 1.5	-67 to +325																																						
		Refer to the performance specifications of the products in this family for detailed description																																								
		Supplied Accessories: 1) Accredited calibration certificate (ISO 17025) 2) Model 6200 mounting stud, qty 1																																								
		Notes: [1] All specifications are at room temperature unless otherwise specified. [2] Measured at 100Hz, 1 g RMS per ISA RP 37.2. [3] Measure using zero-based straight line method, % of F.S. or any lesser range. [4] Do not apply power to this system without current limiting, 20 mA MAX. To do so will destroy the IC charge amplifier. [5] In the interest of constant product improvement, we reserve the right to change specifications without notice. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts.																																								
PHYSICAL Weight Connector Mounting Provision Material, Housing/Connector Sensing Element Element Style		Type Tapped Hole	<table><thead><tr><th colspan="2">ENGLISH</th><th colspan="2">SI</th></tr></thead><tbody><tr><td>0.35</td><td>oz</td><td>10</td><td>grams</td></tr><tr><td>10-32</td><td></td><td>10-32</td><td></td></tr><tr><td>10-32 Tapped hole</td><td></td><td>10-32 Tapped hole</td><td></td></tr><tr><td>Titanium</td><td></td><td>Titanium</td><td></td></tr><tr><td>Ceramic</td><td></td><td>Ceramic</td><td></td></tr><tr><td>Planar Shear</td><td></td><td>Planar Shear</td><td></td></tr></tbody></table>				ENGLISH		SI		0.35	oz	10	grams	10-32		10-32		10-32 Tapped hole		10-32 Tapped hole		Titanium		Titanium		Ceramic		Ceramic		Planar Shear		Planar Shear									
ENGLISH		SI																																								
0.35	oz	10	grams																																							
10-32		10-32																																								
10-32 Tapped hole		10-32 Tapped hole																																								
Titanium		Titanium																																								
Ceramic		Ceramic																																								
Planar Shear		Planar Shear																																								
PERFORMANCE Sensitivity, ± 5% [2] Range for ± 5 Volts Output Frequency Response, ± 5% Frequency Response, ± 10% Resonant Frequency Broad Band Resolution Linearity [3] Maximum Transverse sensitivity Strain Sensitivity @ 250µε			<table><tbody><tr><td>200</td><td>mV/g</td><td>20</td><td>mV/m/s²</td></tr><tr><td>25</td><td>g pk</td><td>245</td><td>m/s² pk</td></tr><tr><td>1 to 5000</td><td>Hz</td><td>1 to 5000</td><td>Hz</td></tr><tr><td>1 to 10000</td><td>Hz</td><td>1 to 10000</td><td>Hz</td></tr><tr><td>> 36</td><td>kHz</td><td>> 36</td><td>kHz</td></tr><tr><td>0.0003</td><td>g RMS</td><td>0.003</td><td>m/s² RMS</td></tr><tr><td>± 1</td><td>% F.S.</td><td>± 1</td><td>% F.S.</td></tr><tr><td>5</td><td>%</td><td>5</td><td>%</td></tr><tr><td>0.002</td><td>g/µε</td><td>0.02</td><td>m/s²/µε</td></tr></tbody></table>				200	mV/g	20	mV/m/s ²	25	g pk	245	m/s ² pk	1 to 5000	Hz	1 to 5000	Hz	1 to 10000	Hz	1 to 10000	Hz	> 36	kHz	> 36	kHz	0.0003	g RMS	0.003	m/s ² RMS	± 1	% F.S.	± 1	% F.S.	5	%	5	%	0.002	g/µε	0.02	m/s ² /µε
200	mV/g	20	mV/m/s ²																																							
25	g pk	245	m/s ² pk																																							
1 to 5000	Hz	1 to 5000	Hz																																							
1 to 10000	Hz	1 to 10000	Hz																																							
> 36	kHz	> 36	kHz																																							
0.0003	g RMS	0.003	m/s ² RMS																																							
± 1	% F.S.	± 1	% F.S.																																							
5	%	5	%																																							
0.002	g/µε	0.02	m/s ² /µε																																							
ENVIRONMENTAL Maximum Shock Temperature Range Seal			<table><tbody><tr><td>±2,000</td><td>g pk</td><td>19620</td><td>m/s² pk</td></tr><tr><td>-67 to +325</td><td>°F</td><td>-55 to +163</td><td>°C</td></tr><tr><td>Hermetic</td><td></td><td>Hermetic</td><td></td></tr></tbody></table>				±2,000	g pk	19620	m/s ² pk	-67 to +325	°F	-55 to +163	°C	Hermetic		Hermetic																									
±2,000	g pk	19620	m/s ² pk																																							
-67 to +325	°F	-55 to +163	°C																																							
Hermetic		Hermetic																																								
ELECTRICAL Supply Current Range [4] Compliance Voltage Range Output Impedence, Typ Bias Voltage Discharge Time Constant Electrical Isolation			<table><tbody><tr><td>2 to 20</td><td>mA</td><td>2 to 20</td><td>mA</td></tr><tr><td>+18 to +30</td><td>Volts</td><td>+18 to +30</td><td>Volts</td></tr><tr><td>100</td><td>Ω</td><td>100</td><td>Ω</td></tr><tr><td>+10 to +13</td><td>VDC</td><td>+10 to +13</td><td>VDC</td></tr><tr><td>0.5 to 1.5</td><td>Sec</td><td>0.5 to 1.5</td><td>Sec</td></tr><tr><td>10</td><td>GΩ, min</td><td>10</td><td>GΩ, min</td></tr></tbody></table>				2 to 20	mA	2 to 20	mA	+18 to +30	Volts	+18 to +30	Volts	100	Ω	100	Ω	+10 to +13	VDC	+10 to +13	VDC	0.5 to 1.5	Sec	0.5 to 1.5	Sec	10	GΩ, min	10	GΩ, min												
2 to 20	mA	2 to 20	mA																																							
+18 to +30	Volts	+18 to +30	Volts																																							
100	Ω	100	Ω																																							
+10 to +13	VDC	+10 to +13	VDC																																							
0.5 to 1.5	Sec	0.5 to 1.5	Sec																																							
10	GΩ, min	10	GΩ, min																																							
		  																																								
		Units on the line drawing are in inches, units in brackets are in millimeters. Refer to 127-3055D7 for more information.																																								
		21592 Marilla Street, Chatsworth, California 91311 Phone: 818.700.7818 Fax: 818.698.0362 www.dytran.com For permission to reprint this content, please contact info@dytran.com																																								