




PROPRIETARY AND CONFIDENTIAL	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF DYTRAN INSTRUMENTS INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF DYTRAN INSTRUMENTS INC. IS PROHIBITED	
MODEL	SENSITIVITY
3056D9T	10 mV/g
3056D10T	20 mV/g
3056D11T	50 mV/g
3056D12T	100 mV/g
3056D13T	200 mV/g
3056D14T	500 mV/g

DWGNO		127-3056D9T		SH	1	REV	A			
REVISIONS										
REV.	ECN	DESCRIPTION					BY/DATE	CHK	APPR	
A	14614	INITIAL RELEASE					KG 12/08/20	RA	DV	

5. OPERATING TEMPERATURE: -67 °F TO +320 °F
[-55 °C TO +160 °C]
TEDS OPERATING TEMPERATURE: -40 °F TO +185 °F
[-40 °C TO +85 °C]


4. MATES WITH DYTRAN 6010AXX OR 6011AXX CABLE (XX=LENGTH IS FEET)




3. WEIGHT: 10 GRAMS (APPROX)

2. ARROW INDICATES ACCELERATION DIRECTION FOR POSITIVE OUTPUT.

1. MATERIAL: TITANIUM ALLOY

NOTES: UNLESS OTHERWISE SPECIFIED

UNLESS OTHERWISE SPECIFIED: INTERPRET DIM & TOL PER ASME Y14.5M - 1994. REMOVE BURRS. COUNTERSINK INTERNAL THDS 90° TO MAJOR DIA. CHAM EXT THDS 45° TO MINOR DIA. THD LENGTHS AND DEPTHS ARE FOR MIN FULL THDS. DIMENSIONS APPLY AFTER FINISHING. ALL MACHINED SURFACES. ✓ TOTAL RUNOUT WITHIN .005. BREAK SHARP EDGES .005 TO .010. MACHINED FILLET RADII .005 TO .015. WELDING SYMBOLS PER AWS A2.4. ABBREVIATIONS PER MIL-STD-12.	UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES. TOLERANCES ARE: <table><tr><td>DECIMALS</td><td>METRIC</td><td>ANGLES</td></tr><tr><td>.XX ±.03</td><td>.X ±.08</td><td>±1°</td></tr><tr><td>.XXX ±.010</td><td>.XX ±0.25</td><td></td></tr></table>			DECIMALS	METRIC	ANGLES	.XX ±.03	.X ±.08	±1°	.XXX ±.010	.XX ±0.25		 Chatsworth, CA		
	DECIMALS	METRIC	ANGLES												
	.XX ±.03	.X ±.08	±1°												
	.XXX ±.010	.XX ±0.25													
	APPROVALS		DATE		TITLE: OUTLINE/INSTALLATION DWG, SINGLE AXIS ACCEL, 320F, ISOLATED, TEDS, 3056D9T SERIES										
	ORIG	KG	12/08/20												
CHK															
APP															
DO NOT SCALE DRAWING		THIRD ANGLE PROJECTION USA 		SIZE B	CAGE CODE 2W033	DWG NO 127-3056D9T	REV A								
				SCALE: 3:1		SHEET 1 OF 1									

Model Number		PERFORMANCE SPECIFICATIONS				DOC NO				
3056D11T						PS3056D11T				
		IEPE ACCELEROMETER				REV B, ECN 16090, 03/02/21				
	• -67 °F TO +325°F OPERATION • BASE ISOLATED • IDEAL LOW FREQUENCY RESPONSE • TEDS FEATURE					This family also includes:				
						Model	Sensitivity (mV/g)	Frequency Response, ±10% (Hz)	Time Constant (Sec)	Operating Temp (°F)
						3056D9T	10	1 to 10000	0.5 to 1.5	-67 to +325
						3056D10T	20	1 to 10000	0.5 to 1.5	-67 to +325
						3056D12T	100	1 to 10000	0.5 to 1.5	-67 to +325
Refer to the performance specifications of the products in this family for detailed description										
Supplied Accessories:										
1) Accredited calibration certificate (ISO 17025)										
2) Model 6200 mounting stud, Qty. 1										
Notes:										
[1] All specifications are at room temperature unless otherwise specified.										
[2] Measured at 100Hz, 1 g RMS per ISA RP 37.2.										
[3] Measure using zero-based straight line method, % of F.S. or any lesser range.										
[4] Do not apply power to this system without current limiting, 20 mA MAX. To do so will destroy the IC charge amplifier.										
[5] In the interest of constant product improvement, we reserve the right to change specifications without notice.										
It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts.										
PHYSICAL		ENGLISH		SI						
Weight	0.35	oz	10	grams						
Connector	10-32		10-32							
Mounting Provision	10-32 Tapped hole		10-32 Tapped hole							
Material, Housing/Connector	Titanium		Titanium							
Sensing Element	Ceramic		Ceramic							
Element Style	Planar Shear		Planar Shear							
PERFORMANCE		ENGLISH		SI						
Sensitivity, ± 5% [2]	50	mV/g	5.1	mV/m/s ²						
Range for ± 5 Volts Output	±100	g pk	±981	m/s ² pk						
Frequency Response, ± 5%	1 to 5000	Hz	1 to 5000	Hz						
Frequency Response, ± 10%	1 to 10000	Hz	1 to 10000	Hz						
Resonant Frequency	> 36	kHz	> 36	kHz						
Broad Band Resolution	0.001	g RMS	0.01	m/s ² RMS						
Linearity [3]	±1	% F.S.	±1	% F.S.						
Maximum Transverse sensitivity	5	%	5	%						
Strain Sensitivity @ 250µε	0.001	g/µε	0.01	m/s ² /µε						
ENVIRONMENTAL		ENGLISH		SI						
Maximum Shock	±2,000	g pk	19620	m/s ² pk						
Temperature Range	-67 to +325	°F	-55 to +163	°C						
TEDS Operating Temperature Range	-40 to +185	°F	-40 to +85	°C						
Seal	Hermetic		Hermetic							
ELECTRICAL		ENGLISH		SI						
Supply Current Range [4]	2 to 20	mA	2 to 20	mA						
Compliance Voltage Range	+18 to +30	Volts	+18 to +30	Volts						
Output Impedance, Typ	100	Ω	100	Ω						
Bias Voltage	+10 to +13	VDC	+10 to +13	VDC						
Discharge Time Constant	0.5 to 1.5	Sec	0.5 to 1.5	Sec						
Electrical Isolation	10	GΩ, min	10	GΩ, min						
TEDS Feature	IEEE 1451.4		IEEE 1451.4							
										
										
										
Units on the line drawing are in inches, units in brackets are in millimeters. Refer to 127-3056D9T for more information.										



21592 Marilla Street, Chatsworth, California 91311 Phone: 818.700.7818 Fax:818.698.0362 www.dytran.com
For permission to reprint this content, please contact info@dytran.com