


ACCELEROMETER MOUNTING ACCESSORIES

Adhesives

Model	Description
6273	Mounting wax, 20 grams




6273

Tools

Model	Description
6239	Vibration probe, 0.5" hex, 6" long, 10-32 tapped hole, aluminum
6591A	Installation and removal wrench, aluminum, 3225E and 3225F series
6725A	Installation and removal wrench, aluminum, 3224A series
6741	Installation and removal wrench, aluminum, 3133A series



6239



6591A



6725A




6741

Adhesive Mounting Bases

Model	Hex Size (in)	Thickness (in)	Mounting Thread	Material
6167	0.375	0.125	2-56	Stainless Steel
6207	0.375	0.156	5-40	Aluminum
6213	0.625	0.260	10-32	Stainless Steel
6221	0.625	0.18	10-32	Aluminum



6167




6207




6213




6221




6222



6226




6228




6243

Mounting Isolation Adapters


Model	Hex Size (in)	Thickness (in)	Mounting Thread	Material
6223	0.375	0.340	10-32	Aluminum
6244	0.375	0.375	10-32	Aluminum
6245	0.625	0.375	10-32	Aluminum
6222	0.375	0.156	5-40	Aluminum
6226	0.625	0.18	10-32	Aluminum
6228	0.50	0.20	10-32	Aluminum
6243	0.375	0.28	10-32	Aluminum
6268	0.312	0.14	5-40	Aluminum
6714	0.56	0.34	4-40	Aluminum




6268




6714



6223



6244



6245

Magnetic Mounting Bases


Model	Hex Size (in)	Thickness (in)	Mounting Thread	Material
6196	0.750	0.400	10-32	Stainless Steel
6199	0.375	0.210	2-56	Stainless Steel
6209	1.00	0.74	10-32	Stainless Steel
6258	0.625	0.390	10-32	Stainless Steel
6265	0.375	0.210	5-40	Stainless Steel
6272	0.625	0.430	10-32	Stainless Steel
6284	0.50	0.430	10-32	Stainless Steel
6295	0.250	0.120	flat surface for adhesive mount	Stainless Steel
6729	0.625	0.505	4-40	Stainless Steel




6196




6199



6209



6258



6265




6272



6284



6295




6729


ACCELEROMETER MOUNTING ACCESSORIES

Studs

Model	Threads			Material
6166	10-32	to	2-56	Stainless Steel
6176	1/4-28	to	1/4-28	Stainless Steel
6200	10-32	to	10-32	Copper Alloy
6200S	10-32	to	10-32	Stainless Steel
6201	10-32	to	1/4-28	Copper Alloy
6203	10-32	to	M6 x 1.0	Copper Alloy
6205	5-40	to	10-32	Copper Alloy
6580	5-40	to	5-40	Copper Alloy



6166




6176




6200



6200S



6201



6203




6205




6580

Triaxial Mounting Blocks


Model	Dimensions (in)	Mounting	Material
6159	0.38 cube	flat surface for adhesive mount	Stainless Steel
6240A	1 cube	10-32	Aluminum
6240S	1 cube	10-32	Stainless Steel
6241	0.75 cube	10-32	Aluminum
6269	0.38 cube	5-40	Aluminum
6552	2.5 cube	1/4-28	Aluminum
6717	1.2 cube	4-40	Aluminum




6159




6240A




6240S




6241



6269




6552




6717

Screws


Model	Thread	Length (in)	Material
6164	6-32	0.750	Stainless Steel
6165	2-56	0.38	Aluminum
6238A1	8-32	0.65	Stainless Steel
6238A2	8-32	0.75	Stainless Steel
6247A2	6-32	0.40	Stainless Steel
6297	6-32	0.54	Aluminum
6523	1/4-28	1.07	Stainless Steel
6524	1/4-28	0.89	Stainless Steel
6535	8-32	0.50	Stainless Steel
6545A1	4-40	0.31	Stainless Steel
6722	M2	0.47	Stainless Steel
6746	4-40	0.31	Stainless Steel
6914	M2	0.79	Stainless Steel




6164




6165




6238A1




6238A2




6247A2



6297



6523




6524




6535




6545A1



6722




6746




6914

Immersion Proof™ and Protective Boots


Model	Hex (in)	Length (in)	Material
6185	0.9	3.4	Viton™
6194	1.1	2.67	Viton™
6529	0.94	3.87	Viton™



6185



6194



6529